

## 21.5" Open Frame Touch Monitor

### Features

- Fanless and rugged design
- High brightness solution: 700 / 1000 nits
- 5W resistive / True flat PCT touch screen
- Resolution 1920 x 1080 dpi
- Open frame mount

### Specifications

High Brightness	700nits	1000nits
<b>DISPLAY</b>		
Size	21.5" TFT (16:9)	
Resolution	1920 x 1080	
Colors	16.2M	16.2M
Luminance	700 cd/m2	1000 cd/m2
Contrast Ratio	2000 : 1	2000 : 1
Viewing Angle (H/V)	176°/176°	176°/176°
<b>POWER REQUIREMENT</b>		
Power Requirement	DC in 12V	
<b>OS SUPPORT</b>		
OS support	Win Pro 7.8.1, 10 / embedded Win 7, 8, 10	
<b>MECHANICAL &amp; ENVIRONMENTAL</b>		
Operation Temp.	0 ~ 50°C	
Storage Humidity	10 ~ 90%, non-condensing	
Mounting	Open frame mount	
Dimension (WxHxD)	TBD	
Weight	TBD	
<b>OPTIONAL</b>		
P/N: 302A170057	700 cd/m2 High Brightness 21.5" LCD panel 1920 x 1080 dpi	
P/N: 3080109001	2M DP cable	
P/N: 3080108001	2M HDMI cable	
P/N: 2320000001	Optical bonding	

<b>ORDERING INFORMATION</b>	
Model No.	Products Description
<b>OM215RJ03</b>	21.5" Fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
<b>OM215PJ03</b>	21.5" Fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
<b>OM215EJ03</b>	21.5" Fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
<b>OM215RJ04</b>	21.5" Fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2
<b>OM215PJ04</b>	21.5" Fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2
<b>OM215EJ04</b>	21.5" Fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2

\*\*If you select 700 cd/m2 high brightness products, please change the model number and specifications in accordance with the rules of encoding.