


### 17" Open Frame Touch Monitor



#### Features

- Fanless and rugged design
- Wide temperature: -20°C ~ 60°C
- High brightness solution: 700 / 1000 / 1500nits
- 5W resistive / True flat PCT touch screen
- Resolution 1280 x 1024 dpi
- Open frame mount

#### Specifications

High Brightness	700nits	1000nits	1500nits
<b>DISPLAY</b>			
Size	17" TFT (4:3)		
Resolution	1280 x 1024		
Colors	16.7M	16.7M	16.7M
Luminance	700 cd/m2	1000 cd/m2	1500 cd/m2
Contrast Ratio	1000 : 1	1000 : 1	1000 : 1
Viewing Angle (H/V)	170°/160°	170°/160°	170°/160°
<b>POWER REQUIREMENT</b>			
Power Requirement	DC in 12V		
<b>OS SUPPORT</b>			
OS support	Win Pro 7.8.1, 10 / embedded Win 7, 8, 10		
<b>MECHANICAL &amp; ENVIRONMENTAL</b>			
Operation Temp.	-20 ~ 60°C		
Storage Humidity	10 ~ 90%, non-condensing		
Mounting	Open frame mount		
Dimension (WxHxD)	TBD		
Weight	TBD		
<b>OPTIONAL</b>			
P/N: 302A170060	700 cd/m2 High Brightness 17" LCD panel 1280 x 1024 dpi		
P/N: 302A17005D	1500 cd/m2 High Brightness 17" LCD panel 1280 x 1024 dpi		
P/N: 3080109001	2M DP cable		
P/N: 3080108001	2M HDMI cable		
P/N: 2320000001	Optical bonding		

<b>ORDERING INFORMATION</b>	
Model No.	Products Description
<b>OM170RK03</b>	17" Wide temp. fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
<b>OM170PK03</b>	17" Wide temp. fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
<b>OM170EK03</b>	17" Wide temp. fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DVI, 1 x USB, 1 x 1.8m VGA cable. 1 x 1.8m USB cable, 1 x DC in external power adapter, 1000 cd/m2
<b>OM170RK04</b>	17" Wide temp. fanless open frame monitor, 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2
<b>OM170PK04</b>	17" Wide temp. fanless open frame monitor, true flat PCT, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2
<b>OM170EK04</b>	17" Wide temp. fanless open frame monitor, true flat 5 wires resistive, 1 x VGA, 1 x DP, 1 x HDMI, 1 x USB, 1 x 1.8m VGA cable, 1 x 1.8m USB cable, DC in power adapter, 1000 cd/m2

**\*\*If you select 700 cd/m2 or 1500 cd/m2 high brightness products, please change the model number and specifications in accordance with the rules of encoding.**